

PRODUCT SPECIFICATIONS

7083B Advanced ComforTech GEL

Construction Belted Harness

All Advanced ComforTech GEL harnesses feature our exclusive polymer gel endoskeleton for unsurpassed user comfort and light weight Aluminum Alloy D-rings. Advanced ComforTech harnesses are specifically configured for Fall Arrest, Work Positioning and Climbing applications.

Features

- Premium breathable padded shoulder yoke with polymer GEL endoskeleton
- Exclusive Aluminum Alloy CamLock torso adjusters
- Proprietary Dorsal D-ring keeper with integrated SRD attachment sleeve
- Contoured removable leg pads with polymer GEL
- Forged Aluminum Alloy D-rings
- Alloy Steel Visi-lock Quick Connect chest buckle
- Alloy Steel Visi-lock Quick Connect leg adjusters
- One Dorsal and two Hip D-rings
- Torso-sewn Waist Support Positioning Pad with polymer GEL endoskeleton and Tool Lanyard connection rings
- Extreme-Duty removable work belt with Aluminum Alloy buckle



7083B
Advanced ComforTech GEL Harness

MATERIALS SPECIFICATIONS

Webbing:	Polyester; Min. 5,000 lbs. Tensile Strength
D-Rings:	Aluminum Alloy and Alloy Steel; Min. 5,000 lbs. Tensile Strength
Buckles/Adjusters:	Aluminum Alloy and Alloy Steel; 3,375 lbs. Min Tensile Strength

PERFORMANCE SPECIFICATIONS

Static Strength:	3,600 lbs. Minimum
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES

Style #	Description
7083BS	Small
7083BM	Medium
7083BL	Large
7083BXL	X Large
7083B2X	2X Large
7083B3X	3X Large

For shoulder and waist size ranges, please see Size Charts page.

RELEVANT STANDARDS

ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.