Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221

	ĺ							
Decla	aration #		Declaration Date			4.20.15		
Tested It	em # 72	7630LE	30' L	eading Ed	lge Contr	actor	Cable	SRD
Addit	ional Items Co 7276	_	ler this Declarat	ion:				
Ale		-	clares that th ents of the fo					ity with
			ANSI Z	359.14-20	014			
	Confo	ormity Assess	sment Method	in accordance	e with ANSI/	ISEA 125	5-2014	
	Lev	el 1	Lev	vel 2 X		evel 3		
C	L evel 1 : FallTeo Dutside the Sco EC Standard 1	ope of	Withi	2: FallTech Lab in the Scope of andard 17025:		ac	credited	3rd Party Lab to .7025:2005
Supportin Documen	_	PC-0582	210125-ASLa1 210125-ASLa2 210125-ASLa3	210125-ASLc1 210125-ASLc2 210125-ASLc3	210125-ASLh	2 21012	5-ASLw1 5-ASLw2 5-ASLw3	PC-0993
	Autho	rized Signat	ure		fin	<u>, , , , , , , , , , , , , , , , , , , </u>	-	
Name	Dustin I	lawkins	Title	VP Business	Development		Date	12.4.16

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com



Testing. Advising. Assuring.

April 22, 2015

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Peter Mahbubani

Quality Engineer Supervisor

Subject: Attestation of Witnessing Testing

Exova OCM Job # 350485
FallTech P.O.: 13825
Report No.: PC-0582
Base Part No. 727630LE

Description: 30' Leading Edge, Cable, Self-Retracting Device

Attached to Test Weight

Dear Mr. Mahbubani:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- Date of Testing:
 - April 16, 2015
- Exova OCM Test Witness:
 - Robert Fortner
- FallTech Test Operators:
 - Peter Mahbubani
 - Yesbet Sierra
- · Specification:
 - ANSI Z359.14-2012 4.2.1, 4.2.3, 4.2.5, 4.2.6, 4.2.8.1, 4.2.8.2, 4.2.8.3
- Equipment Calibration Interval
 - 1 year



Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
PC-0582	4/20/2015	727630LE	30' Leading Edge, Cable, Self- Retracting Device	318149 318234 318240 318215 318224 318249 318145 318170 318247 318225 318246 318248 318144 318241 318244 318166 318167 318167 318167	Pass

Test Witness Signature: (Signed for and on behalf of Exova-OCM)

Robert Fortner
Technician
Mechanical Laboratory

Approval Signature:

Bruce K. Sauer
Technical Director

(Signed for and on behalf of Exova-OCM)

Approval Signature: (Signed for and on behalf of Exova-OCM)
Thomas J. (Tom) Parsons

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.

Manager

Quality / Technical Services








FallTech Test Report									
Test Report Number	PC-0582								
Report Prepared For	FallTech								
Initiated By	Dan Redden Test Specification ANSI Z359.14-2012 4.2.1, 4.2.3, 4.2.5, 4.2.6, 4.2.7, 4.2.8.1, 4.2.8.2, 4.2.8.3						2.6, 4.2.7,		
Base Part #	727630LE	Description	n	30' Leading Edge	, Cable, Self-	Retracting D	evice		
Proposed Part #	N/A	Built By Whom		Production		BOM	No		
Test Request #	PC-0582	Date Recei	ved	4/15/2015	Date	e Complete	4/16/2015		
Test Operator	Peter Mahbubani	Test Opera	itor	Yesbet Sierra					

	Material/Sample Identification
Sample ID	Description
318149	30' Leading Edge, Cable, Self-Retracting Device
318234	30' Leading Edge, Cable, Self-Retracting Device
318240	30' Leading Edge, Cable, Self-Retracting Device
318215	30' Leading Edge, Cable, Self-Retracting Device
318224	30' Leading Edge, Cable, Self-Retracting Device
318249	30' Leading Edge, Cable, Self-Retracting Device
318145	30' Leading Edge, Cable, Self-Retracting Device
318170	30' Leading Edge, Cable, Self-Retracting Device
318247	30' Leading Edge, Cable, Self-Retracting Device
318225	30' Leading Edge, Cable, Self-Retracting Device
318246	30' Leading Edge, Cable, Self-Retracting Device
318248	30' Leading Edge, Cable, Self-Retracting Device
318144	30' Leading Edge, Cable, Self-Retracting Device
318241	30' Leading Edge, Cable, Self-Retracting Device
318244	30' Leading Edge, Cable, Self-Retracting Device
318166	30' Leading Edge, Cable, Self-Retracting Device
318167	30' Leading Edge, Cable, Self-Retracting Device
318243	30' Leading Edge, Cable, Self-Retracting Device
2861306	30' Leading Edge, Cable, Self-Retracting Device
2861138	30' Leading Edge, Cable, Self-Retracting Device
2861286	30' Leading Edge, Cable, Self-Retracting Device

This laboratory is accredited in accordance with the recognized international Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).



Page 1 of 27 FLT-08 Rev. D 10/1/2014





FallTech Test Report									
Test Report Number	PC-0582	Date	4/20/2015	Rev	2	Rev Date	11/10/2015		
Report Prepared For	FallTech								
Initiated By	Dan Redden Test Specification ANSI Z359.14-2012 4.2.1, 4.2.3, 4.2.5, 4.2.6, 4.2.7, 4.2.8.1, 4.2.8.2, 4.2.8.3						2.6, 4.2.7,		
Base Part #	727630LE	Description	n	30' Leading Edge	e, Cable, Self-	Retracting D	evice		
Proposed Part #	N/A	Built By W	hom	Production	•	BOM	No		
Test Request #	PC-0582	Date Recei	ved	4/15/2015	Date	e Complete	4/16/2015		

Test Summary								
Test Specification	Test (Criteria	Test Result	Pass/Fail				
	Arrest Distance	Class A ≤ 24" Class B <u>≤</u> 54"	15"	Pass				
ANSI Z359.14-2012	Max Arrest Force	≤ 1800 Lbf	1173.4 lbF	Pass				
4.2.1	Avg Arrest Force	Class A ≤ 1350 Lbf Class B ≤ 900 Lbf	737.8 lbF	Pass				
	Retraction Tension	1.25 Lbf - 25 Lbf ≤ 24" Extended	5.6 lbF	Pass				
	Arrest Distance	Class A < 24" Class B < 54"	19.75"	Pass				
ANSI Z359.14-2012	Max Arrest Force	≤ 1800 Lbf	1266.5 lbF	Pass				
4.2.1	Avg Arrest Force	Class A ≤ 1350 Lbf Class B ≤ 900 Lbf	773.1 lbF	Pass				
	Retraction Tension	1.25 Lbf - 25 Lbf ≤ 24" Extended	6.2 lbF	Pass				
	Arrest Distance	Class A ≤ 24" Class B ≤ 54"	15.3"	Pass				
ANSI Z359.14-2012	Max Arrest Force	≤ 1800 Lbf	1094.3 lbF	Pass				
4.2.1	Avg Arrest Force	Class A ≤ 1350 Lbf Class B ≤ 900 Lbf	734.0 lbF	Pass				
	Retraction Tension	1.25 Lbf - 25 Lbf ≤ 24" Extended	5.8 lbF	Pass				
ANSI Z359.14-2012 4.2.3	Dynamic Strength	4' Fall w/ 300 Lb Test Weight; Weight Shall Not Strike the Ground	Did not strike ground	Pass				
	Line Constituent Strength	≥ 1000 Lbf	1011 lbF	Pass				
ANSI Z359.14-2012 4.2.3	Dynamic Strength	4' Fall w/ 300 Lb Test Weight; Weight Shall Not Strike the Ground	Did not strike ground	Pass				
4.2.3	Line Constituent Strength	≥ 1000 Lbf	1008.7 lbF	Pass				
ANSI Z359.14-2012 4.2.3	Dynamic Strength	4' Fall w/ 300 Lb Test Weight; Weight Shall Not Strike the Ground	Did not strike ground	Pass				
	Line Constituent Strength	≥ 1000 Lbf	1011.7 lbF	Pass				

This laboratory is accredited in accordance with the recognised international Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).



Page 2 of 27 FLT-08 Rev. D 10/1/2014

Pass



4.2.6

ANSI Z359.14-2012

4.2.7

ANSI Z359.14-2012

4.2.7

ANSI Z359.14-2012

4.2.7

ANSI Z359.14-2012 4.2.8.1

ANSI Z359.14-2012 4.2.8.1

ANSI Z359.14-2012 4.2.8.1

Retraction Tension

Horizontal Orientation

Horizontal Orientation

Horizontal Orientation

Arrest Distance

Max Arrest Force

Avg Arrest Force

Retraction Tension

Arrest Distance

Max Arrest Force

Avg Arrest Force

Retraction Tension

Arrest Distance

Max Arrest Force

Avg Arrest Force

Retraction Tension

Retraction Tension SRD-LE

Retraction Tension SRD-LE

Retraction Tension SRD-LE

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

		- UT 1	T 1 D				
		FallTech	n Test Re	eport			
Test Report Number	PC-0582	Date	4/20/2015	Rev	2	Rev Date	11/10/201
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Speci	ification	ANSI Z359.14-20 4.2.8.1, 4.2.8.2, 4		2.3, 4.2.5, 4.2	.6, 4.2.7,
Base Part #	727630LE	Descriptio	n	30' Leading Edge	e, Cable, Self-	Retracting D	evice
Proposed Part #	N/A	Built By W	Built By Whom			ВОМ	No
Test Request #	PC-0582	Date Rece	ived	4/15/2015	Dat	e Complete	4/16/2015
ANSI Z359.14-2012 4.2.5	Static Strength		000 Lbf 0 Seconds	3026.8	lbF	Р	ass
ANSI Z359.14-2012 4.2.5	Static Strength		000 Lbf 0 Seconds	3031.3	lbF	Р	ass
ANSI Z359.14-2012 4.2.5	Static Strength		000 Lbf 0 Seconds	3034.7 lbF		Pass	
ANSI Z359.14-2012 4.2.6	Retraction Tension		bf - 25 Lbf Extended	6.4 lbF		Р	ass
ANSI Z359.14-2012 4.2.6	Retraction Tension		1.25 Lbf - 25 Lbf ≤ 24" Extended 6.2 lbF		Р	ass	
ANSI Z359.14-2012	Retraction Tension	1.25 L	bf - 25 Lbf	6.6 lb	ıF	P	ass

< 24" Extended

Shall Retract Without

Stopping

Shall Retract Without

Stopping

Shall Retract Without

Stopping Class A ≤ 24"

Class B ≤ 54" <u><</u> 1800 Lbf

Class A < 1575 Lbf

Class B ≤ 1125 Lbf 1.25 Lbf - 25 Lbf

≤ 24" Extended Class A < 24"

Class B ≤ 54"

<u><</u> 1800 Lbf

Class A < 1575 Lbf

Class B ≤ 1125 Lbf 1.25 Lbf - 25 Lbf

≤ 24" Extended Class A ≤ 24"

Class B ≤ 54" ≤ 1800 Lbf

Class A < 1575 Lbf

Class B < 1125 Lbf 1.25 Lbf - 25 Lbf

≤ 24" Extended

6.6 lbF

Retracted Without Stopping

Retracted Without Stopping

Retracted Without Stopping

27.5"

1247.1 lbF

843.3 lbF

6.2 lbF

29.8"

934.9 lbF

763.0 lbF

6.4 lbF

31.0"

1073.5 lbF

790.5 lbF

6.4 lbF

This laboratory is accredited in accordance with the recognized international Standard ISO/IEC 17025/2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).



FLT-08 Rev. D 10/1/2014 Page 3 of 27





		FallTech	n Test Re	eport				
Test Report Number	PC-0582	Date	4/20/2015	Rev	2	Rev Date	11/10/2015	
Report Prepared For	FallTech	•		•		•	•	
Initiated By	Dan Redden	Test Spec	Lest Specification		ANSI Z359.14-2012 4.2.1, 4.2.3, 4.2.5, 4.2.6, 4.2.7, 4.2.8.1, 4.2.8.2, 4.2.8.3			
Base Part #	727630LE	Description	n	30' Leading Edg	ge, Cable, Se	elf-Retracting D	Device	
Proposed Part #	N/A	Built By W	/hom	Production		вом	No	
Test Request #	PC-0582	Date Rece	Date Received		D	ate Complete	4/16/2015	
	Arrest Distance		s A <u><</u> 24" s B <u><</u> 54"	29.	3"	ı	Pass	
ANSI Z359.14-2012	Max Arrest Force	<u><</u> 1	800 Lbf	1160.	4 lbF	ı	Pass	
4.2.8.2	Avg Arrest Force		≤ 1575 Lbf ≤ 1125 Lbf	801.	7 lbF	!	Pass	
	Retraction Tension	_	bf - 25 Lbf Extended	6.2	lbF	ı	Pass	
ANSI Z359.14-2012 4.2.8.2	Arrest Distance		s A <u><</u> 24" s B <u><</u> 54"	28.	3"	ı	Pass	
	Max Arrest Force	<u>−</u> ≤ 1800 Lbf		1164.2 lbF		!	Pass	
	Avg Arrest Force	Class A ≤ 1575 Lbf Class B ≤ 1125 Lbf		777.4	1 lbF		Pass	
	Retraction Tension	1.25 Lbf - 25 Lbf < 24" Extended		4 1	bF		Pass	
	Arrest Distance	Class A ≤ 24" Class B ≤ 54"		24.	3"	1	Pass	
ANSI Z359.14-2012	Max Arrest Force	≤ 1800 Lbf		1560.3 lbF			Pass	
4.2.8.2	Avg Arrest Force		≤ 1575 Lbf ≤ 1125 Lbf	813.7 lbF		ı	Pass	
	Retraction Tension	_	bf - 25 Lbf Extended	5.6 lbF		ı	Pass	
	Arrest Distance	Clas	s A <u><</u> 24" s B <u><</u> 54"	32.5"		1	Pass	
ANSI Z359.14-2012	Max Arrest Force		800 Lbf	1135.9 lbF		ı	Pass	
4.2.8.3	Avg Arrest Force		≤ 1575 Lbf ≤ 1125 Lbf	705.4 lbF		1	Pass	
	Retraction Tension	1.25 L	bf - 25 Lbf Extended	5.0 lbF		ı	Pass	
	Arrest Distance	Clas	s A <u><</u> 24" s B <u><</u> 54"	27.5"			Pass	
ANSI Z359.14-2012	Max Arrest Force		800 Lbf	1008.	7 lbF	ı	Pass	
4.2.8.3	Avg Arrest Force		≤ 1575 Lbf ≤ 1125 Lbf	730.8	3 lbF	1	Pass	
	Retraction Tension		bf - 25 Lbf Extended	6.4	lbF	1	Pass	

This laboratory is accredited in accordance with the recognized international Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).



Page 4 of 27 FLT-08 Rev. D 10/1/2014



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

Test Report Number	PC-0582	Date	4/20/2015	Rev	2	Rev Date	11/10/2015	
Report Prepared For	FallTech							
Initiated By	Dan Redden	Test Spec	ification	ANSI Z359.14-2 4.2.8.1, 4.2.8.2,		4.2.3, 4.2.5, 4.	2.6, 4.2.7,	
Base Part #	727630LE	Description	n	30' Leading Edg	e, Cable, Se	If-Retracting D	evice	
Proposed Part #	N/A	Built By W	/hom	Production		ВОМ		
Test Request #	PC-0582	Date Rece	ived 3	4/15/2015	Da	te Complete	4/16/2015	
			Υ	4	Lancia de la companya			
	Arrest Distance	1	Class A ≤ 24" Class B ≤ 54"		27.3"		Pass	
ANSI Z359.14-2012	Max Arrest Force	≤ 18	≤ 1800 Lbf		1040.4 lbF		ass	
4.2.8.3	Avg Arrest Force		Class A ≤ 1575 Lbf Class B ≤ 1125 Lbf		741.8 lbF		ass	
	Retraction Tension		1.25 Lbf - 25 Lbf < 24" Extended		5.6 lbF		Pass	
		Co	onclusion					
	FallTech P/N 727630LE Se	elf-retracting Dev	ice meets the r	equirements of AN	ISI Z359.14-20	012.		
		Report Signa	ntories and A	Approval				
Lab Quality Manager		gay Spe	nholz		Date	12/8	3/2015	

This laboratory is accredited in accordance with the recognized international Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).







FallTech Test Report							
Test Report Number	PC-0993	Date	11/30/2016	Rev	Rev D	Date	
Report Prepared For	FallTech						
Initiated By	Warren Faber	Test Specification ANSI Z359.14-2014; 4.2.1, 4.2.6					
Base Part #	727620LE	Description	n	20' Contractor SR	L-LE		
Proposed Part #	727620LE	Built By W	hom	Development	E	BOM No	
Test Request #	PC-0993	Date Recei	ved	11/28/2016	Date Comp	olete 11/29/201	
Test Operator	Yesbet Sierra	Test Opera	tor	Jay Sponholz			

Material/Sample Identification						
Sample ID	Description					
500019	20' Contractor SRL-LE					
500020	20' Contractor SRL-LE					
500021	20' Contractor SRL-LE					

Test Summary									
Test Specification	Test C	riteria	Test Result	Pass/Fail					
	Arrest Distance	Class A <u><</u> 24" Class B <u><</u> 54"	19.1"	Pass					
	Max Arrest Force	≤ 1800 Lbf	718.7 lbF	Pass					
	Avg Arrest Force	Class A ≤ 1350 Lbf Class B ≤ 900 Lbf	576.0 lbF	Pass					
	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	9.2 lbF	Pass					
ANSI Z359.14-2014 4.2.1, 4.2.6	Retraction Tension 20% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	9.6 lbF	Pass					
4.2.1, 4.2.0	Retraction Tension 40% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	12.8 lbF	Pass					
	Retraction Tension 60% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	12.8 lbF	Pass					
	Retraction Tension 80% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	13.4 lbF	Pass					
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	14.0 lbF	Pass					
	Arrest Distance	Class A ≤ 24" Class B ≤ 54"	21.5"	Pass					
	Max Arrest Force	<u>≤</u> 1800 Lbf	897.6 lbF	Pass					
	Avg Arrest Force	Class A <u><</u> 1350 Lbf Class B <u><</u> 900 Lbf	593.6 lbF	Pass					
	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	8.8 lbF	Pass					
ANSI Z359.14-2014 4.2.1, 4.2.6	Retraction Tension 20% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	9.4 lbF	Pass					
4.2.1, 4.2.0	Retraction Tension 40% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	11.4 lbF	Pass					
	Retraction Tension 60% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	11.2 lbF	Pass					
	Retraction Tension 80% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	11.4 lbF	Pass					
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf < 24" Extended	12.4 lbF	Pass					





FallTech Test Report						
Test Report Number	PC-0993	Date	11/30/2016	Rev		Rev Date
Report Prepared For	FallTech			·		
Initiated By	Warren Faber	Test Speci	fication	ANSI Z359.14-20	14; 4.2.1, 4.2.	6
Base Part #	727620LE	Description	า	20' Contractor SRL-LE		
Proposed Part #	727620LE	Built By W	Built By Whom			BOM No
Test Request #	PC-0993	Date Recei	ved	11/28/2016	Date	e Complete 11/29/2016
		Test	Summary			
Test Specification	Tes	t Criteria		Test Re	sult	Pass/Fail
	Arrest Distance		A <u><</u> 24" B <u><</u> 54"	22.2	1	Pass
	Max Arrest Force	<u><</u> 18	≤ 1800 Lbf		bF	Pass
	Avg Arrest Force		Class A ≤ 1350 Lbf Class B ≤ 900 Lbf		bF	Pass
	Retraction Tension 0% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		F	Pass
ANSI Z359.14-2014 4.2.1, 4.2.6	Retraction Tension 20% Extracted		1.25 Lbf - 25 Lbf < 24" Extended		ρF	Pass
	Retraction Tension 40% Extracted	_	of - 25 Lbf Extended	11.2	ρF	Pass
	Retraction Tension 60% Extracted		of - 25 Lbf Extended	11.8	ρF	Pass
	Retraction Tension 80% Extracted	_	of - 25 Lbf Extended	13.4 lbF		Pass
	Retraction Tension 100% Extracted		of - 25 Lbf Extended	14.0 li	ρF	Pass
		Co	nclusion			
Fall	Tech P/N 727620LE 20' Cont	ractor SRL-LE mee	ets the requirem	nents of ANSI Z359.1	4-2014. (4.2.1,	4.2.6)
		Report Signa	tories and A	pproval		
Lab Quality Manager	- 1 10			Date	11/30/2016	

Not Required

Witnessed by

N/A

Date





FallTech Test Report							
Test Report Number	PC-0993	Date	11/30/2016	Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Warren Faber	aber Test Specification ANSI Z359.14-2014; 4.2.1, 4.2.6					
Base Part #	727620LE	Description	1	20' Contractor SR	L-LE		
Proposed Part #	727620LE	Built By W	hom	Development		BOM	No
Test Request #	PC-0993	Date Recei	ved	11/28/2016	Date	e Complete	11/29/2016

Test Information						
Description of Test	Dynamic Performance and Retraction Tension Test, Self-retracting Device					
Test Method		ANSI Z359.14	-2014 4.2.1, 4.2.6			
Acceptance Criteria		ANSI Z359.14-2014 3.1.9, 3.1.6				
Test Procedure	TI-001					
Conditioning Requirements	Not Applicable	Actual Conditions Not Applicable			Not Applicable	
Time Removed from Conditioning	Not Applicable	Time Tested Not Applicable			Not Applicable	
Test Environment	66.0°F / 44.0% RH					
Test By	Yesbet Sierra, Jay Sponholz		Test Da	ate	11/29/2016	

Equipment Used					
Equipment Used	Size/Type	Control Number	Calibration Date		
Load Cell	10,000 Lbs	342183	5/2/2016		
Test Weight	282 Lbs	TW282	4/16/2014		
Altimeter	100 Ft	ALE-87283	6/7/2016		
Force Gauge	30 Lbf x 0.2 Lbf	5675	6/1/2016		

Test Results						
Sample ID	Characteristic	Criteria	Test Data	Pass/Fail		
	Arrest Distance	Class A ≤ 24" Class B ≤ 54"	19.1"	Pass		
	Max Arrest Force	≤ 1800 Lbf	718.7 lbF	Pass		
	Avg Arrest Force Class A ≤ 1350 Lbf Class B ≤ 900 Lbf	576.0 lbF	Pass			
	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	9.2 lbF	Pass		
500019	Retraction Tension 20% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	9.6 lbF	Pass		
	Retraction Tension 40% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	12.8 lbF	Pass		
	Retraction Tension 60% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	12.8 lbF	Pass		
	Retraction Tension 80% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	13.4 lbF	Pass		
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended	14.0 lbF	Pass		



		FallTech	n Test Re	port		
Test Report Number	PC-0993	Date	11/30/2016	Rev		Rev Date
Report Prepared For	FallTech					
Initiated By	Warren Faber	Test Spec	ification	ANSI Z359.14-2014; 4.2.1, 4.2.		6
Base Part #	727620LE	Descriptio	Description		RL-LE	
Proposed Part #	727620LE	Built By W	/hom	Development		BOM No
Test Request #	PC-0993	Date Rece	ived	11/28/2016	Date	Complete 11/29/2016
	Arrest Distance		s A <u><</u> 24" s B <u><</u> 54"	21.5"		Pass
	Max Arrest Force	≤1	800 Lbf	897.6 lbF		Pass
	Avg Arrest Force		\ <u><</u> 1350 Lbf B <u><</u> 900 Lbf	593.6	lbF	Pass
	Retraction Tension 0% Extracted	_	.bf - 25 Lbf Extended	8.8 lk	ρF	Pass
500020	Retraction Tension 20% Extracted	_	.bf - 25 Lbf Extended	9.4 lk	ρF	Pass
	Retraction Tension 40% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended		11.4 lbF		Pass
	Retraction Tension 60% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended		11.2 lbF		Pass
	Retraction Tension 80% Extracted	1.25 Lbf - 25 Lbf ≤ 24" Extended		11.4 lbF		Pass
	Retraction Tension 100% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		bF	Pass
	Arrest Distance	Class A ≤ 24" Class B ≤ 54"		22.2"		Pass
	Max Arrest Force	≤ 1800 Lbf		897.2 lbF		Pass
	Avg Arrest Force		Class A \leq 1350 Lbf Class B \leq 900 Lbf		lbF	Pass
	Retraction Tension 0% Extracted		1.25 Lbf - 25 Lbf < 24" Extended		ρF	Pass
500021	Retraction Tension 20% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		bF	Pass
	Retraction Tension 40% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		bF	Pass
	Retraction Tension 60% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		bF	Pass
	Retraction Tension 80% Extracted		1.25 Lbf - 25 Lbf ≤ 24" Extended		bF	Pass
	Retraction Tension 100% Extracted	_	.bf - 25 Lbf Extended	14.0	bF	Pass

End of Report





Gravitec Systems Inc. 21291 Urdahl Road NW Poulsbo, WA 98370

Testing Report Summary

Gravitec Systems, Inc. performed testing to on the following product for FallTech in February, 2015.

Model/Part Number: 30' Contractor SRL-LE

Lot/ Batch:

November 2014

Description: This self-retracting device is a SRL-LE with a wire rope line element designed for the Class A specifications and leading-edge capabilities.

Serial Numbers:

318148	318199	318204	318211	318217	318229
318186	318201	318205	318214	318218	318230
318187	318202	318208	318215	318219	318231
318196	318203	318210	318216	318228	318237

Standard: ANSI Z359.14-2014, Safety Requirements for Self-Retracting Devices for Personal Fall Arrest and Rescue Systems

Test Procedure: 4.2.2 Dynamic Performance of SRL-LE: Edge Test

This procedure was performed for the environmental conditioning of Ambient Dry, Heat, Cold, and Wet as defined in 4.2.8.

Acceptance Criteria: 3.1.9 Dynamic Performance , when tested in accordance to 4.2.2 for SRL-LE Class A devices

Referenced Test Reports:

210125-ASLa1	210125-ASLc1	210125-ASLh1	210125-ASLw1
210125-ASLa2	210125-ASLc2	210125-ASLh2	210125-ASLw2
210125-ASLa3	210125-ASLc3	210125-ASLh3	210125-ASLw3

Summary of Results: The results of the testing meets or exceeds the acceptance criteria. The testing for this procedure meets requirements for Qualification Testing as defined in ANSI Z359.7-2011. Qualification testing is testing conducted on new or revised products consisting of a minimum of 3 test samples per test procedure. This is in contrast to Verification Testing, which consists of a minimum of 1 sample and is intended to ensure continued product compliance of an existing product that has gone through Qualification Testing in the past.

- Important Notes: 1) This is a summary of tests and is not intended to replace the individual test reports provided for each of the procedures performed.
 - 2) Refer to test reports referenced above for testing details and for actual test results.
 - 3) The results stated on test reports only apply to the exact item or product tested.
 - 4) This Edge Test is one test procedure of a suite of procedures required for SRL-LE.

Proper labeling of a product as compliant with the ANSI/ASSE Z359 standard is the responsibility of the manufacturer. Per ANSI/ASSE Z359.7, a product may be labeled as being compliant with the ANSI/ASSI Z359 standard only when the product meets or exceeds all applicable requirements and specifications of the standard.

The manufacturer is responsible for identifying the testing to be performed and for determining the appropriateness of the testing regiment for their needs. This includes the quantity of samples tested, the selection of representative samples from the client's product, and the scope of the project in general.

Gravitec's Testing Laboratory meets the requirements of international standard ISO/IEC 17025:2005 with accreditation through ANSI-ASQ National Accreditation Board/ACLASS. The types of tests to which this accreditation applies is contained in the Scope of Accreditation.

Laboratory Signature: Larry Cimino, PE

Signature:

This laboratory is accredited to ISO 17025 by ACLASS ANSI-ASQ National Accreditation Board for tests conducted under its scope of accreditation.

Testing to the sections referenced in this report summary does not infer compliance to the standard in its entirety.