

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B1020145

Declaration Date

10/22/2020

Tested Item #

8144QCSM

FT-Iron FBH 3D Construction Belted, Dual Size S/M, QC
Legs and Chest

Additional Items Conforming Under this Declaration:

8144QCXS 8144QCLXL 8144QC2X3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with
the requirements of the following product standard(s):

ANSI Z359.11-2014

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

☐

Level 2

X

Level 3

☐

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2042

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

10/22/2020



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017
Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2042	Rpt. Date	10/21/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144QCSCM			Part No. Revision		A	
Part Description	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2042			Date Complete		10/20/2020	
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
5569831	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569842	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569834	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569840	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569836	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569838	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569830	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569843	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569832	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569841	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569828	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569833	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569839	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569835	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5569837	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest

Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3638.3 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.33"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3645.6 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

FallTech Test Report

Test Report No.	PC-2042	Rpt. Date	10/21/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144QCSM			Part No. Revision		A	
Part Description	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2042			Date Complete		10/20/2020	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3644.7 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.47"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3839.0 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3648.4 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3644.8 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

FallTech Test Report

Test Report No.	PC-2042	Rpt. Date	10/21/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144QCSCM			Part No. Revision		A	
Part Description	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2042			Date Complete		10/20/2020	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4256.5 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.9"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4640.2 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.8°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.4"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4572.0 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.6°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	12.3"	Pass

FallTech Test Report

Test Report No.	PC-2042	Rpt. Date	10/21/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144QCSM			Part No. Revision		A	
Part Description	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2042			Date Complete		10/20/2020	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2192.7 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	4.4°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	1654.9 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.2°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2040.4 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	1.4°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

FallTech Test Report

Test Report No.	PC-2042	Rpt. Date	10/21/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8144QCSM			Part No. Revision		A	
Part Description	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest						
Test Request No.	PC-2042			Date Complete		10/20/2020	

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.7	Lanyard Parking Attachment Element	Disengagement Load ≤ 120 Lbf	Previously Tested and Passed under PC-1897	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8144QCSM Rev. A meets the requirements of ANSI Z359.11-2014

Test Exceptions

* Harness has been dynamically tested and subjected to forces of 5,000 Lbs. or more. Energy absorbing properties inherent to the harness prevented residual force readings equal to or greater than the 3,600 Lbs. required by the standard.

Report Signatories and Approval

Lab Quality Manager		Date	10/21/2020
Witnessed by	Not Required	Date	N/A